# MASONRY SAW

# TBE350 ★★

Cutting depth up to 110 mm





Swivelling saw head enables 45° mitre cuts.



Two robust castors ensure total manoeuvrability in the deployment location.



Angle stop provided for cuts of 30° to 90°

The TBE350\*\* table saw offers an uncompromising price-performance ratio as well as high flexibility through numerous settings and application options. A sturdy saw table with an-

ti-slip support guarantees clean cuts. The swivelling saw head allows mitre cuts to be made with ease. Detachable table feet and transport wheels ensure trouble-free transport.



# **System & Accessories**

## **Technical data**

Saw blade		
Max. cutting depth	110 mm	
Max. saw blade Ø	350 mm	
Cutting length	600 mm	
Saw blade speed	2800 rpm	
Saw blade holder Ø	25.4 mm	

#### Drive

Drive / motor	Electric
Output	2.2 kW
Standard voltage/frequency	230 V / 50 Hz
Optional voltage/frequency	110 V / 60 Hz
Engine cooling	Air cooling
Saw blade drive	Direct

#### Design

20019.1
Infinitely adjustable cutting depths
Angle cutting function (angle stop)
Mitre cutting function
Cap cutting function
Water tank made from powder-coated steel
Electric water pump
Dismantable

## **Dimensions & Weight**

Length	1140 mm
Width	640 mm
Height	1230 mm
Weight	79 kg

## System & Accessories

Masonry TBE350**	
10981423	Masonry saw TBE350** / 230 V
10981424	Masonry saw TBE350** / 110 V

