

FLOOR SAW

FSD1274★★★ 3-SPEEDS

Cutting depth up to 480 mm



Three speeds for ideal rotational speeds and optimised lifetime



Safe repositioning of the saw thanks to neutral position

Floor saw with powerful and economical, built-in longitudinal 74 PS Kubota turbo diesel engine. The cutting shaft in the oil bath minimises maintenance work and protects the belts from slurry. An automatic On/Off function simplifies handling and reduces cooling water consumption.

The hydraulic drive system with no belts or chains to adjust and the hydraulic handle adjustment ensure effortless and time-saving work.

System & Accessories

Technical data

Saw blade	
Max. cutting depth	480 mm
Max. saw blade Ø	1200 mm
No Load saw blade speed	1700 / 1250 / 975 1/min.
Saw blade holder Ø	25,4 mm
Carrier Ø	11,5 mm
Reference circle Ø	57,4 mm

Drive

Drive/motor	Diesel
Type	Kubota
Output	30 55 kW / 74 PS
Fuel	Diesel
Fuel tank	34,2 l
Engine cooling	water cooling
Feed	Hydraulic
Blade drive	directly flange-mounted
Feed speed	0-76 m/min

Design

Electro-hydraulic cutting depth adjustment
Electro-mechanical cutting depth stop
Hydraulic adjustable handles
Left/right cutting function
Tool cooling using water fork
Engine cover
3 speed gear box with neutral position

Dimensions & Weight

Length	1620 mm
Width	927 mm
Height	1420 mm
Weight	990 kg

System & Accessories

Floor saw FSD1274***	
10989900	Floor Saw FSD1274*** 3 Speed (1200 mm guard)

Accessories

10985254	650 mm (26") blade guard
10989836	750 mm (30") blade guard
10989838	900 mm (36") blade guard
	1000 mm (42") blade guard
	1200 mm (48") blade guard

Diesel particle filter and transformation set on request