FLOOR SAW FSG620***

Cutting depth up to 230 mm





Exceptionally easy handling due to neatly arranged control panel.



Controlled work thanks to digital operating hours counter and reliable petrol gauge.



Blade guard side change in just a few steps.

Thanks to its intelligent weight distribution, the FSG620** provides for excellent cutting behaviour and the

left- and right-handed cutting function enhances flexibility.



System & Accessories

Technical data

Saw blade	
Max. cutting depth	230 mm
Max. saw blade Ø	600 mm
Saw blade speed	2120 rpm
Saw blade holder Ø	25.4 mm
Carrier Ø	11.5 mm
Reference circle Ø	57.4 mm

Drive

Drive/motor	Petrol
Туре	Honda
Output	13 kW / 18 PS
Fuel	Lead free
Fuel tank	7.6
Engine cooling	Air cooling
Feed	Hydraulic
Blade drive	Via V-belt
Feed speed	0-24 m/min

Design

Manual, stepless cut depth setting via a spindle	
Tool cooling using water fork	
Left/right cutting function	
25 I water tank	

Dimensions & Weight

Length	840 mm
Width	580 mm
Height	1030 mm
Weight	184 kg

System & Accessories

Floor saw FSG620***		
10984041	Floor saw FSG620***	
Accessories		
10984389	Green concrete kit with 350 mm blade guard and transformation set (3000 rpm)	

