FLOOR SAW FSD930**

Cutting depth up to 350 mm





Easy, controlled work thanks to clear control panel.



Water regulation for optimum tool cooling and useful lighting always within reach.



Exact alignment of the machine using cut indicator.

Thanks to intelligent weight distribution, the FSD930** features excellent cutting behaviour. The hydraulic feed

drive and electro-hydraulic cutting depth adjustment permit convenient and ergonomic operation.



System & Accessories

Technical data

| Saw blade | |
|--------------------|----------|
| Max. cutting depth | 350 mm |
| Max. saw blade Ø | 900 mm |
| Saw blade speed | 1400 rpm |
| Saw blade holder Ø | 25.4 mm |
| Carrier Ø | 11.5 mm |
| Reference circle Ø | 57.4 mm |

Drive

| Drive/motor | Diesel |
|----------------|---------------|
| Туре | Deutz |
| Output | 22 kW / 30 PS |
| Fuel | Diesel |
| Fuel tank | 22.8 |
| Engine cooling | Air cooling |
| Feed | Manual |
| Blade drive | Via V-belt |
| Feed speed | 0-61 m/min |

Design

| Electric-hydraulic cutting depth adjustment |
|---|
| Cutting depth indicator |
| Tool cooling using water fork |
| Left/right cutting function |
| Corner flush cutting function |

Dimensions & Weight

| Length | 1170 mm |
|--------|---------|
| Width | 820 mm |
| Height | 1250 mm |
| Weight | 655 kg |

System & Accessories

| Floor saw FSD930*** | | |
|---------------------|--|--|
| 10984042 | Floor saw FSD930*** | |
| Accessories | | |
| 10984390 | Green concrete kit with 450 mm blade guard and transformation set (2300 rpm) | |

Diesel particle filter and transformation set on request.

