

DRILL MOTOR

DME22SU★★

Core drilling up to Ø 180 mm



Three-speed transmission for optimum rotational speeds.



Dry drilling with the included M16 adapter.



Comes in a handy transport case.

The DME22SU** drill motor is ideal for electrical and installation work. It features a 3-speed transmission and variable speed setting with soft start.

Integrated overload cut-outs and the PRCD safety switch ensure safe working. Dry drilling is also possible with the included M16 adapter.

System & Accessories

Technical data

Drill Motor DME 22SU**		
Voltage/Frequency	230 V / 50-60 Hz	110 V / 50-60 Hz
Type no.	10993027	10993028
Drill diameter range	20–180 mm	
Nominal power	2.2 kW	
Nominal current	9.5 A	18 A
Load speed	400/750/1550 rpm	
No load speed	850/1650/3450 rpm	
Motor cooling	Luft	
Tool attachment (external)	1 ¼"	
Tool attachment (internal)	½"	
Operation	Hand-held / rig-based	
Application	Wet / dry	
Electronic overload cut-out	•	
Mechanical overload cut-out	•	
PRCD protection switch	•	
Drill rig attachment	Clamping collar 60 mm	

Dimensions & Weight

Length	552 mm
Width	110 mm
Height	150 mm
Weight	6.0 kg

System & Accessories

Core drilling system with DRU160*** Drill rig	
10993027	El. Drill motor DME22SU**
10987400	Drill rig DRU160***
977619	Fastening bolt assembly

Accessories

400439	Extension 1/2" 100 mm
359475	Extension 1/2" 200 mm
359476	Extension 1/2" 300 mm
889232	Extension 1/2" 400 mm
707230	Extension 1/2" 500 mm
378198	Extension 1 1/4" 100 mm
359471	Extension 1 1/4" 200 mm
359472	Extension 1 1/4" 300 mm
359473	Extension 1 1/4" 400 mm
359474	Extension 1 1/4" 500 mm
10983964	Dust vacuum adaptor M16
10983845	Centering spike 120 mm
10986189	Centering spike 233 mm
10986190	Strap wrench