# FLOOR GRINDER FGE530★★★

Three-phase, max. grinding width 530 mm





Maximum durability thanks to robust design.



The powerful motor enables the efficient machining of larger areas.



Time-saving, simple and safe tool change using patented quick fixing system.

The FGE530\*\*\* impresses with simple operation thanks to an ergonomic control panel, a fixed speed and low noise/vibration values. The planetary drive guarantees perfectly consistent and cost-effective grinding results. A

quick tool fixing system and dismantable machine parts enable fast system setup and easy transport. Thanks to the floating cover in conjunction with the reliable extraction system, dust free working is ensured.



# **System & Accessories**

#### **Technical data**

Max. grinding width	530 mm
Grinding disc width	3 x 230 mm
Grinding disc speed	715 rpm
Grinding pressure	94.7 kg

#### Design

3 Grinding discs	
Planetery drive system (belt)	
Detachable machine parts	

#### Drive

Drive/motor	Electric
Туре	Busck
Power	4 kW
Voltage/Frequency	400 V / 50 Hz
Current	8.2 A

## **Dimensions & Weight**

790 mm	
570 mm	
1310 mm	
131 kg	
102 kg	
	570 mm 1310 mm 131 kg

## **System & Accessories**

10991317

Floor Grinder FGE530***		
10990286	Floor Grinder FGE530*** 400V (50 Hz)	
Accessorie	s	
10990289	Dust collection system VCE4000D*** 400V (50 Hz)	
Werkzeug		
10991635	Set-heavy removal GT0*** (9 x single segment)	
10991312	Set-removal GT1*** (9 x single segment)	
10991313	Set-removal GT1*** (9 x double segment)	
10991314	Set-rough-grinding GT2*** (9 x single segment)	
10991315	Set-rough-grinding GT2*** (9 x double segment)	
10991316	Set-smooth-grinding GT3*** (9 x single segment)	

Set-smooth-grinding GT3\*\*\* (9 x double segment)

