

DRIVE PPH20★★

Output 20 kw



Ergonomically arranged control panel



Safe due to high quality electronic components



Manometer display for main and feed cycle

The 2-stage control ensures optimum cutting speeds for all applications. A simple and uncomplicated

drive with product features reduced to the essentials.

System & Accessories

Technical data

Electric motor

Output	20 kW
--------	-------

Hydraulics

Pressure stages	2
-----------------	---

2 feed circuits	Gear pump
-----------------	-----------

Main circuit	Double gear pump
--------------	------------------

Output

Stage 1	33 l/min at 260 bar
---------	---------------------

Stage 2	40 l/min at 210 bar
---------	---------------------

Electrical equipment

Voltage	200 V / 400 V / 480 V
---------	-----------------------

Frequency	50 Hz / 60 Hz
-----------	---------------

Current consumption (400V / 50 Hz)	32 A
------------------------------------	------

Dimensions

Length	720 mm
--------	--------

Width	475 mm
-------	--------

Height	988 mm
--------	--------

Weight	140 kg
--------	--------

System & Accessories

Drive unit PPH20**

10983600*	Drive unit PPH20S / 380-420V / 50Hz
-----------	-------------------------------------

976206	Hose package 5pieces 8 m FD
--------	-----------------------------

975672	Hose package 2pieces 8 m FF (feed)
--------	------------------------------------

Accessories

973072	El.-plug CEE 32/5pol.
--------	-----------------------

999578	On/Off valve for wire sawing
--------	------------------------------

* Different voltage types are available upon request.